



TL55 5T



Curvas de cargas
Load diagrams
Lastkurven
Courbes de charges
Curve di carico

55 m


24	25	26	28	30	30,4	33	35	37	39	40	43	45	48	50	52	55
2500	2500	2500	2500	2500	2500	2278	2123	1984	1861	1804	1648	1557	1434	1360	1292	1200

m
Kg 

50 m


24	25	26	28	30	33	34,5	35	37	39	40	43	45	48	50
2500	2500	2500	2500	2500	2500	2500	2468	2310	2169	2104	1928	1824	1684	1600

m
Kg 

45 m


24	25	26	28	30	33	35	37	38,8	39	40	43	45
2500	2500	2500	2500	2500	2500	2500	2500	2500	2489	2416	2217	2100

m
Kg 

40 m


24	25	26	28	30	33	35	37	38,5	39	40
2500	2500	2500	2500	2500	2500	2500	2500	2500	2472	2400

m
Kg 

35 m



24	25	26	28	30	33	35
2500	2500	2500	2500	2500	2500	2500

m
Kg 

15	18	20,2	21	24	27	30	33	35
5000	5000	5000	4822	4135	3606	3186	2844	2650

m
Kg 


Mástil / Reacciones
Masts / Reactions
Maste / Eckdrücke
Mat / Réactions
Torre / Reazioni



25	E: 55TL/HEM 1.20 M39/M39 8/8
25	F: CAMPANA 4m 1.20/1.50 M39/M42 8/8
38	J: CAMPANA 10m 1.20/1.70 M39/M45 8/8
33	K: S17 1.70 M45/M45 8/8
31	L: S17 1.70 M45/M45 16/8
B090	N: S17-S21 M45/M45 8/8
B080	P: S21 M45/M45 16/8

Mástil / Reacciones
Masts / Reactions
Maste / Eckdrücke
Mat / Réactions
Torre / Reazioni

25	E: 55TL/HEM 1.20 M39/M39 8/8
25	F: CAMPANA 4m 1.20/1.50 M39/M42 8/8
38	J: CAMPANA 10m 1.20/1.70 M39/M45 8/8
33	K: S17 1.70 M45/M45 8/8
31	L: S17 1.70 M45/M45 16/8
B090	N: S17-S21 M45/M45 8/8
B080	P: S21 M45/M45 16/8



**Mecanismos
Mechanisms
Antriebe
Mécanismes
Meccanismi**

25 Hp (18,5 Kw)							
	m/min	8	31	62	4	16	32
	Kg	2500	2500	1500	5000	5000	2600
	Kw	18,5	18,5	18,5	18,5	18,5	18,5
	m/min	30 / 60			30 / 60		
	Kw	3			3		
	r.p.m	0,3	0,6	0,8	0,3	0,6	0,8
	Nm	2 x 40			2 x 40		
	m/min	20			20		
	Kw	2 x 2,2			2 x 2,2		


	400 V 50 Hz	31 kVA
---	----------------	--------

* 25 Hp INV (18,5 Kw)							
	m/min	8	31	62	4	16	31
	Kg	2500	2500	1500	5000	5000	2600
	Kw	18,5	18,5	18,5	18,5	18,5	18,5


* 33 Hp INV (24 Kw)							
	m/min	40	60	80	20	30	40
	Kg	2500	2000	1500	5000	5000	3000
	Kw	24	24	24	24	24	24














- * Opcional / Optional / Opzionale /
-  Elevación / Hoisting / Heben / Levage / Sollevamento
 -  Distribución / Trolleying / Katzfahren / Distribution / Distributions
 -  Orientación / Slewing / Schwenken / Orientation / Rotazione
 -  Traslacion / Travelling / Schienenfahren / Translation / Traslazione

Bloque de contrapeso
Counterweight blocks
Gegengewichtsblöcke
Bloc de contrepoid
Blocco di contrappeso

	55 m			50 m			45 m			40 m			35 m		
	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C
	5	1	1	5	-	2	5	-	1	4	-	2	3	1	1
	13750 Kg			13200 Kg			12350 Kg			10900 Kg			9150 Kg		

Bloque lastre de base
Base ballast block
Grundballastblöcke
Bloc de lest de base
Blocco di zavorra alla base

	24,80 m	30,70 m	34,80 m	40,80 m	50,60 m
	3,8 x 3,8 m	45,6 t	60,8 t	-	-
4,5 x 4,5 m City	-	-	60,8 t	76 t	-
4,5 x 4,5 m S-60	-	-	60,8 t	76 t	121,6 t

			L (m)	W (m)	H (m)	Kg
Pluma tramo primero / Jib heel section Ausleger-Anlenkstück / Pied de flèche Settore articolato di braccio		1	11,74	1	1,85	2314
Elemento intermedio de pluma Intermediate jib section Ausleger-Zwischenstück Élément interm. de flèche Spezzzone di braccio	    	2 3 4 5 6 7	10 11,5 6,5 5 5 5	1 1 1 1 1 1	1,8 1,8 1,8 1,3 1,19 1,18	1224 1064 502 312 262 206
Contrapluma / Counter-jib Gegenausleger / Contre-flèche Controbraccio			11,49	0,32	1,83	3240
Elemento de torre / Tower section Turmstück / Elément de mât Elemento di torre			11,8 4,0	1,2 1,2	1,38 1,38	3782 1300
Bloque de contrapeso Counterweight blocks Gegengewichtsblöcke / Bloc de contrepoids Blocco di contrappeso		A B C	2,94 2,94 1,70	0,30 0,18 0,18	1,25 1,25 1,25	2300 1400 850
Bloque lastre de base / Base ballast block Grundballastblöcke / Bloc de lest de base Blocco di zavorra alla base			4,4	1,2	0,3	3800
Gancho y Carro / Hook and Trolley Lasthaken - Laufkatze / Crochet - Chariot Gancio e Carrello			0,75 0,96	0,12 1,10	1,40 0,62	160 180
Cabeza de torre / Tower head Turmspitze / Porte - flèche Testa di torre			3,14	1,8	1,7	3200
Viga principal base / Main base beam Hauptträger für fundamentkreuz Poutre de châssis de base Trave principale della base			5,72	0,67	0,65	1560
Semiviga secundaria base Half base beam / Halbträger für fundamentkreuz Semipoutre de châssis de base Semitrave secundaria della base			2,77	0,45	0,665	1500
Cabina y soporte / Cabin and support Kabine und wartungs plattform Cabine et support / Cabina e supporto			2,3	0,94	2,35	450

ESPECIFICACIONES SUJETAS A MODIFICACIONES SIN PREVIO AVISO.
Specifications subject to modification without notice.
Obiges kann ohne berstaendigung geaendert werden.
Specifications susceptibles de modification sans avis préalable.
Specifiche suscettibili di variazioni senza preavviso.

DECLINAMOS TODA RESPONSABILIDAD DERIVADA DE LA INFORMACION PROPORCIONADA.
This information is supplied without liability.
Sämtliche Angaben erfolgen ohne Gewähr.
Ces renseignements sont sans garantie.
Le indicazioni contenute si intendono salvo errori ed omissioni.